

M/s. Nasima Enterprise**Tenderer's Quoted Price**

Tenderer's Quoted Price

Total Estimated Cost (BDT)	Percentage (-5% to +5%)	Offered Amount (in figures) (BDT)	Offered Amount (in words) (BDT)
499737.000	-5.000	474750.150	Four Lakh Seventy-Four Thousand Seven Hundred And Fifty Point One Five
	Grand Total:	474750.150	Four Lakh Seventy-Four Thousand Seven Hundred And Fifty Point One Five

This Tenderer's Quoted Price is Electronically Signed by Mr. Nazmul Hasan on behalf of M/s. Nasima Enterprise

M/s. Nasima Enterprise

Priced Bill of Quantities (BOQ)

Unit Rate Basis

Estimate by the Procuring Entity

Item no.	Group	Item Code (if any)	Description of Item	Unit	Quantity	Unit rates or prices (in figures) (BDT)	Unit rates or prices (in words) (BDT)	Amount (in figure) (BDT)	Amount (in words) (BDT)	Select 'YES' to see the Grand Total
1	Civil	15.1.1	Minimum 12 mm thick cement sand (F.M. 1:2) plaster (1:4) with fresh cement to both inner and outer surface of wall, finishing the corner and edges including washing of sand, cleaning the surface, curing at least for 7 days, cost of water, electricity, scaffolding and other charges etc. all complete in all respect as per drawing and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) ground floor.	sqm	125.407	299.001	Two Hundred And Ninety-Nine Point Zero Zero One	37496.818	Thirty-Seven Thousand Four Hundred And Ninety-Six Point Eight One Eight	Yes
2	Civil	16.2.1	Interior standard acrylic emulsion paint (plastic or matt finish) of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container; applying to interior wall and ceiling with surface preparation including cleaning, drying, making free from dirt, grease, wax, removing all chalked and scaled materials, fungus, mending good the surface defects using sand paper	sqm	131.404	258.001	Two Hundred And Fifty-Eight Point Zero Zero One	33902.363	Thirty-Three Thousand Nine Hundred And Two Point Three Six Three	Yes

			and necessary scaffolding; applying necessary interior sealer of specified brand on prepared surface; then applying necessary interior putty of specified brand for levelling, spot filling, crack filling and cutting by sand paper/zero water paper; finally applying 2 coats of interior emulsion paint spreading by brush/roller/spray & necessary scaffolding etc. upto desired finishing, elapsing specified time for drying or recoating; all complete in all floors and accepted by the Engineer-incharge.							
3	Civil	11.1.2.1	Supplying and making door and window frames (Chowkat) for all floors in/c wall side grove cutting, moulding by CNC machine or any other means with matured seasoned wood of required size including painting two coats of coal tar to the surface in contact with wall, fitting and fixing in position etc. all complete and accepted by the Engineer-incharge. (All sizes of wood are finished).	cum	0.210	145620.001	One Lakh Forty-Five Thousand Six Hundred And Twenty Point Zero Zero One	30580.200	Thirty Thousand Five Hundred And Eighty Point Two	Yes
4	Civil	12.1.2.2	"Supplying, fitting and fixing of 38 mm thick well matured seasoned (moisture content should be between 12% to 16%) solid wood single leaf door shutter having stile section 100mm x 38mm, top rail section 125mm x 38mm, lock rail section 100mm x 38mm and bottom rail section 225mm	sqm	8.354	8296.001	Eight Thousand Two Hundred And Ninety-Six Point Zero Zero One	69304.792	Sixty-Nine Thousand Three Hundred And Four Point Seven Nine Two	Yes

			from minimum 250mm wide plank) with 4nos 100mm long, 3mm thick hinge, 12mm dia 250mm long tower bolt, 12mm dia 200mm long socket bolt, 2nos 150mm long handle, hinged cleats and buffer blocks. All complete in all floors and accepted by the Engineer-in-charge. (All sizes of wood are finished)							
5	Civil	06.4.5	Supplying, fitting and fixing foreign made polished pocelain/ mirror polished homogeneous floor tiles complying BDS ISO 13006: 2015, water absorption ≤ 0.5%, modulus of rupture (MOR) ≥ 35 N/mm ² , irrespective of color &/or design, with 20 mm thick cement sand (F.M. 1.2) mortar (1:4) base and raking out the joints with white cement including cutting and laying the tiles in proper way and finishing with care etc. all complete and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) In ground floor. Polished pocelain/ mirror polished 800 mm x 800 mm floor tiles	sqm	91.450	1952.001	One Thousand Nine Hundred And Fifty-Two Point Zero Zero One	178510.491	One Lakh Seventy-Eight Thousand Five Hundred And Ten Point Four Nine One	Yes
6	Civil	14.15.1	Supplying, fitting, fixing of aluminium sliding fly proof Netting shutter as per the U.S. Architectural Aluminium Manufacturer's Association (AAMA) standard specification and BDS 1879:2014 having 2.0 mm thick outer frame (size 38mm x 38mm), minimum 1.2 mm thick mosquito net	sqm	8.922	3798.001	Three Thousand Seven Hundred And Ninety-Eight Point Zero Zero One	33885.764	Thirty-Three Thousand Eight Hundred And Eighty-Five Point Seven Six Four	Yes

			shutter frame mesh section (42.2 mm x13.2mm). All aluminium members will be anodized to aluminium bronze/ silver/ss/black colour with a coat not less than 15 microns in thickness or powder coated to any colour with a coat not less than 25 microns in thickness and density of 4 mg per square cm etc. including all accessories like wheel, sealent, rubber, bolts and nuts keeping provision for fitting fiber mesh including labour charge for fitting of accessories, making grooves and mending good damages, carriage, and electricity, all complete in all respect as per drawing and accepted by the Engineer-in-charge. Anodized to any colour							
7	Civil	26.32.2	Supplying, fitting and fixing of best quality CP self closing pillar cock without mixer (SensorType /Push Type) with necessary hardware etc. complete approved and accepted by the Engineer- in-charge. Push Type Self closing pillar cock	each	3.000	1366.001	One Thousand Three Hundred And Sixty-Six Point Zero Zero One	4098.003	Four Thousand And Ninety-Eight Point Zero Zero Three	Yes
8	Civil	26.38.2	Moving type 150 mm CP shower head	each	2.000	2276.001	Two Thousand Two Hundred And Seventy-Six Point Zero Zero One	4552.002	Four Thousand Five Hundred And Fifty-Two Point Zero Zero Two	Yes

Civil	26.01.7	"Supplying, fitting and fixing of European type country made best quality glazed porcelain combi closet (two piece), including plastic seat cover with soft closing ,cistern system, water consumption 6 litre, siphon wash down/ siphon jet single or dual flushing system which reduce water consumption, hygienic glaze in toilet bowl ,glaze in inner waste line, round bowl, outlet range 280~305 mm. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. The fixture should be placed in position preparing the base with cement concrete and with wire mesh or rods if necessary, in all floors including making holes wherever required and mending good	each	2.000	22075.001	Twenty- Two Thousand And Seventy- Five Point Zero Zero One	44150.002	Forty-Four Thousand One Hundred And Fifty Point Zero Zero Two	Yes
-------	---------	--	------	-------	-----------	---	-----------	--	-----

			the damages and fitting, fixing, finishing, complete with all necessary fittings and connection approved and accepted by the Engineer- in-charge. Approx. 702~ 750x 380~412 mm size, minimum 40.0 kg of weight, Equivalent to COTTO: C118 / RAK: Shino or similar brand"							
10	Civil	26.18.1	Supplying, fitting and fixing of best quality double bowl stainless steel sink with heavy type CI or steel brackets, 12 mm dia C.P. chain plug, 40 mm dia C.P. waste, 40 mm dia PVC waste pipe with brass coupling (750 mm length) including making hole in walls and floors and mending good the damages, finishing etc. all complete approved and accepted by the Engineer-in-charge. Approx. 1160 x 500 mm size double bowl with sink tray (Standard)	each	1.000	8486.001	Eight Thousand Four Hundred And Eighty-Six Point Zero Zero One	8486.001	Eight Thousand Four Hundred And Eighty-Six Point Zero Zero One	Yes

11	Civil	12.8.1	Supplying, fitting and fixing of 40mm thick Wood Plastic Composite (WPC) door shutter (minimum inner wall thickness 6mm and hinge side wall thickness 15mm) having door frame section 150mm x 62mm weighing 16.7kg/sqm with 4nos 100mm long, 3mm thick hinge, 1 no round lock, 2nos 150mm long handle, hinged cleats and carrying the same to the site and local carriage etc. All complete in all floors and accepted by the Engineer-in-charge.	each	2.000	17698.001	Seventeen Thousand Six Hundred And Ninety-Eight Point Zero Zero One	35396.002	Thirty-Five Thousand Three Hundred And Ninety-Six Point Zero Zero Two	Yes
12	Civil	26.12.4	"Supplying, fitting and fixing of country made glazed vitreous W/ H wash basin excluding pedestal. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. The mean value of water absorption shall not be greater than 0.5% of the ware when dry. When tested with chemical solutions The materials used for making glaze shall not contain lead compound. In case of certain coloring oxides used for making colored glaze, the lead content, if any,	each	4.000	4448.001	Four Thousand Four Hundred And Forty-Eight Point Zero Zero One	17792.004	Seventeen Thousand Seven Hundred And Ninety-Two Point Zero Zero Four	Yes

shall not exceed 5 percent of the weight of the glaze materials. Appliances shall be clearly and indelibly marked at a prominent place, visible even after the appliances are installed with the following: a) manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. Over Counter: Approx. 560 X 475 mm size, minimum weight 10.0 kg The fixture should be placed in position with heavy type C.I. Brackets. 30 mm dia PVC waste water pipe with brass coupling (not exceeding 750 mm in length), basin waste with chain plug including making holes in walls and floors and fitting with wall, screws and mending good the damages, finishing etc. all complete approved and accepted by the Engineer-in-charge."

13	Civil	21.2.3	"EXHAUST FAN Providing and fixing of following axial flow AC capacitor type wall mounted exhaust fan complete with blade, steel frame standard wall louver shutter, PVC insulated connecting wire etc. complete as required including cutting wall and mending good the	each	1.000	1583.001	One Thousand Five Hundred And Eighty-Three Point Zero Zero One	1583.001	One Thousand Five Hundred And Eighty-Three Point Zero Zero One	Yes
----	-------	--------	---	------	-------	----------	--	----------	--	-----

direction of the
Engineer. 12""
Exhaust fan plastic
body (foreign made
accepted /
approved by the
Engineer)."

Grand
Total: 499737.443

Four Lakh
Ninety-
Nine
Thousand
Seven
Hundred
And Thirty-
Seven
Point Four
Four
Three

This Priced Bill of Quantities (BOQ) is Electronically Signed by Mr. Nazmul Hasan on behalf of M/s. Nasima Enterprise

DHAKA WATER SUPPLY & SEWERAGE AUTHORITY

Office of the Executive Engineer
Civil Maintenance Division
Dhaka WASA, Dhaka
6th floor, WASA Bhaban
98 Kazi Nazrul Islam avnue, Dhaka.

Name of the Work: Repair and maintenance works of building (Shitalakshya) at Duaripara WASA officers' quarter compound, Dhaka.

Item No.	Group	PWD 2022	Description of Items of Works	Unit	Quantity	Unit rates or prices	Amount
1	Civil	15.1.1	Minimum 12 mm thick cement sand (F.M. 1.2) plaster (1:4) with fresh cement to both inner-and outer surface of wall, finishing the corner and edges including washing of sand, cleaning the surface, curing at least for 7 days, cost of water, electricity, scaffolding and other charges etc. all complete in all respect as per drawing and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) ground floor.	sqm	125.407	299.001	37,496.818
2	Civil	16.2.1	Interior standard acrylic emulsion paint (plastic or matt finish) of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container; applying to interior wall and ceiling with surface preparation including cleaning drying, making free from dirt, grease, wax, removing all chalked and scaled materials, fungus, mending good the surface defects using sand paper and necessary scaffolding; applying necessary interior sealer of specified brand on prepared surface; then applying necessary interior putty of specified brand for levelling, spot filling, crack filling and cutting by sand paper/zero water paper; finally applying 2 coats of interior emulsion paint spreading by brush/roller/spray & necessary scaffolding etc. upto desired finishing, elapsing specified time for drying or recoating; all complete in all floors and accepted by the Engineer-incharge.	sqm	131.404	258.001	33,902.363
3	Civil	11.1.2.1	Supplying and making door and window frames (Chowkat) for all floors in/c wall side grove cutting, moulding by CNC machine or any other means with matured seasoned wood of required size including painting two coats of coal tar to the surface in contact with wall, fitting and fixing in position etc. all complete and accepted by the Engineer-in-charge. (All sizes of wood are finished).	cmu	0.210	145620.001	30,580.200
4	Civil	12.1.2.2	Supplying, fitting and fixing of 38 mm thick well matured seasoned (moisture content should be between 12% to 16%) solid wood single leaf door shutter having stile section 100mm x 38mm, top rail section 125mm x 38mm, lock rail section 100mm x 38mm and bottom rail section 225mm x 38mm (made from minimum 250mm wide plank) with 4nos 100mm long, 3mm thick hinge, 12mm dia 250mm long tower bolt, 12mm dia 200mm long socket bolt, 2nos 150mm long handle, hinged cleats and buffer blocks. All complete in all floors and accepted by the Engineer-in-charge. (All sizes of wood are finished)	sqm	8.354	8296.001	69,304.792

Arifan

Bala

5	Civil	06.4.5	Supplying, fitting and fixing foreign made polished pocelain/ mirror polished homogeneous floor tiles complying BDS ISO 13006: 2015, water absorption $\leq 0.5\%$, modulus of rupture (MOR) ≥ 35 N/mm², irrespective of color &/or design , with 20 mm thick cement sand (F.M. 1.2) mortar (1:4) base and raking out the joints with white cement including cutting and laying the tiles in proper way and finishing with care etc. all complete and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) In ground floor. Polished pocelain/ mirror polished 800 mm x 800 mm floor tiles	sqm	91.450	1952.001	178,510.491
6		14.15.1	Supplying, fitting, fixing of aluminium sliding fly proof Netting shutter as per the U.S. Architectural Aluminium Manufacturer's Association (AAMA) standard specification and BDS 1879:2014 having 2.0 mm thick outer frame (size 38mm x 38mm), minimum 1.2 mm thick mosquito net shutter frame mesh section (42.2 mm x13.2mm). All aluminium members will be anodized to aluminium bronze/silver/ss/black colour with a coat not less than 15 microns in thickness or powder coated to any colour with a coat not less than 25 microns in thickness and density of 4 mg per square cm etc. including all accessories like wheel, sealent, rubber, bolts and nuts keeping provision for fitting fiber mesh including labour charge for fitting of accessories, making grooves and mending good damages, carriage, and electricity, all complete in all respect as per drawing and accepted by the Engineer-in-charge. Anodized to any colour	sqm	8.922	3798.001	33,885.765
7	Civil	26.32.2	Supplying, fitting and fixing of best quality CP self closing pillar cock without mixer (SensorType /Push Type) with necessary hardware etc. complete approved and accepted by the Engineer- in- charge. Push Type Self closing pillar cock	each	3.00	1366.001	4,098.003
8		26.38.2	Moving type 150 mm CP shower head	each	2.00	2276.001	4,552.002
9		26.01.7	Supplying, fitting and fixing of European type country made best quality glazed porcelain combi closet (two piece) , including plastic seat cover with soft closing ,cistern system, water consumption 6 litre, siphon wash down/siphon jet single or dual flushinging system which reduce water consumption, hygienic glaze in toilet bowl ,glaze in inner waste line, round bowl, outlet range 280~305 mm. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. The fixure should be placed in position preparing the base with cement concrete and with wire mesh or rods if necessary, in all floors including making holes wherever required and mending good the damages and fitting, fixing, finishing, complete with all necessary fittings and connection approved and accepted by the Engineer- in- charge. Approx. 702~ 750x 380~412 mm size, minimum 40.0 kg of weight, Equivalent to COTTO: C118 / RAK: Shino or similar brand	each	2.00	22075.001	44,150.002

Handwritten signature

Handwritten signature

10		26.18.1	Supplying, fitting and fixing of best quality double bowl stainless steel sink with heavy type CI or steel brackets, 12 mm dia C.P. chain plug, 40 mm dia C.P. waste, 40 mm dia PVC waste pipe with brass coupling (750 mm length) including making hole in walls and floors and mending good the damages, finishing etc. all complete approved and accepted by the Engineer-in-charge. Approx. 1160 x 500 mm size double bowl with sink tray (Standard)	each	1.00	8486.001	8,486.001
11		12.8.1	Supplying, fitting and fixing of 40mm thick Wood Plastic Composite (WPC) door shutter (minimum inner wall thickness 6mm and hinge side wall thickness 15mm) having door frame section 150mm x 62mm weighing 16.7kg/sqm with 4nos 100mm long, 3mm thick hinge, 1 no round lock, 2nos 150mm long handle, hinged cleats and carrying the same to the site and local carriage etc. All complete in all floors and accepted by the Engineer-in-charge.	each	2.000	17698.001	35,396.002
12		26.12.4	Supplying, fitting and fixing of country made glazed vitreous W/H wash basin excluding pedestal. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. The mean value of water absorption shall not be greater than 0.5% of the ware when dry. When tested with chemical solutions The materials used for making glaze shall not contain lead compound. In case of certain coloring oxides used for making colored glaze, the lead content, if any, shall not exceed 5 percent of the weight of the glaze materials. Appliances shall be clearly and indelibly marked at a prominent place, visible even after the appliances are installed with the following: a) manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. Over Counter: Approx. 560 X 475 mm size, minimum weight 10.0 kg The fixture should be placed in position with heavy type C.I. Brackets. 30 mm dia PVC waste water pipe with brass coupling (not exceeding 750 mm in length), basin waste with chain plug including making holes in walls and floors and fitting with wall, screws and mending good the damages, finishing etc. all	nos	4.00	4448.001	17,792.004
13	Civil	21.2.3	EXHAUST FAN Providing and fixing of following axial flow AC capacitor type wall mounted exhaust fan complete with blade, steel frame standard wall louver shutter, PVC insulated connecting wire etc. complete as required including cutting wall and mending good the damages as per direction of the Engineer. 12" Exhaust fan plastic body (foreign made accepted / approved by the Engineer).	each	1.00	1583.001	1,583.001

Total: 499,737.444

Say 499,737

In word: (Four lac ninty nine thousand seven hundred thirty seven) taka only

১০/১০/২০
রাজিয়া সুলতানা
উপ-সহকারী প্রকৌশলী
সি এম বিভাগ
ঢাকা ওয়াশা।

১০/১০/২০
মুজা সাহা
নির্বাহী প্রকৌশলী
সিএম বিভাগ
ঢাকা ওয়াশা