

NADIYA ENTERPRISE**Priced Bill of Quantities (BOQ)****Unit Rate Basis**

Estimate by the Procuring Entity

Item no.	Group	Item Code (if any)	Description of Item	Unit	Quantity	Unit rates or prices (in figures) (BDT)	Unit rates or prices (in words) (BDT)	Amount (in figure) (BDT)	Amount (in words) (BDT)	Select 'YES' to see the Grand Total
1	Civil	15.1.1	Minimum 12 mm thick cement sand (F.M. 1:2) plaster (1:4) with fresh cement to both inner-and outer surface of wall, finishing the corner and edges including washing of sand, cleaning the surface, curing at least for 7 days, cost of water, electricity, scaffolding and other charges etc. all complete in all respect as per drawing and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) ground floor.	sqm	125.507	299.001	Two Hundred And Ninety-Nine Point Zero Zero One	37526.718	Thirty-Seven Thousand Five Hundred And Twenty-Six Point Seven One Eight	Yes
2	Civil	16.2.1	Interior standard acrylic emulsion paint (plastic or matt finish) of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container; applying to interior wall and ceiling with surface preparation including cleaning drying, making free from dirt, grease, wax, removing all chalked and scaled materials, fungus, mending good the	sqm	381.844	258.001	Two Hundred And Fifty-Eight Point Zero Zero One	98516.133	Ninety-Eight Thousand Five Hundred And Sixteen Point One Three Three	Yes

			surface defects using sand paper and necessary scaffolding; applying necessary interior sealer of specified brand on prepared surface; then applying necessary interior putty of specified brand for levelling, spot filling, crack filling and cutting by sand paper/zero water paper; finally applying 2 coats of interior emulsion paint spreading by brush/roller/spray & necessary scaffolding etc. upto desired finishing, elapsing specified time for drying or recoating; all complete in all floors and accepted by the Engineer-in-charge.							
3	Civil	16.3.2	Premium synthetic enamel paint of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container, having high water resistance, high bondability, flexibility property; using specified brand thinner applying to metallic or wooden surface by brass/roller/spray in two coats over single coat anti-corrosive coating including cleaning, drying, making free from dirt, grease, wax, removing all chalked and scaled materials, all complete in all floors and accepted by the Engineer-in-charge.	sqm	100.372	238.001	Two Hundred And Thirty-Eight Point Zero Zero One	23888.636	Twenty-Three Thousand Eight Hundred And Eighty-Eight Point Six Three Six	Yes
4	Civil	11.1.2.1	Supplying and making door and window frames	cum	0.150	145620.001	One Lakh Forty-Five Thousand	21843.000	Twenty-One Thousand	Yes

			grove cutting, moulding by CNC machine or any other means with matured seasoned wood of required size including painting two coats of coal tar to the surface in contact with wall, fitting and fixing in position etc. all complete and accepted by the Engineer-in-charge. (All sizes of wood are finished).				And Twenty Point Zero Zero One	And Forty-Three		
5	Civil	12.1.2.2	"Supplying, fitting and fixing of 38 mm thick well matured seasoned (moisture content should be between 12% to 16%) solid wood single leaf door shutter having stile section 100mm x 38mm, top rail section 125mm x 38mm, lock rail section 100mm x 38mm and bottom rail section 225mm x 38mm (made from minimum 250mm wide plank) with 4nos 100mm long, 3mm thick hinge, 12mm dia 250mm long tower bolt, 12mm dia 200mm long socket bolt, 2nos 150mm long handle, hinged cleats and buffer blocks. All complete in all floors and accepted by the Engineer-in-charge. (All sizes of wood are finished)"	sqm	8.454	8296.001	Eight Thousand Two Hundred And Ninety-Six Point Zero Zero One	70134.392	Seventy Thousand One Hundred And Thirty-Four Point Three Nine Two	Yes
6	Civil	18.2.1.2	Supplying, fitting and fixing 12 mm thick burma teak (BT) veneered board/ ply board/ particle board in walling with best quality and well seasoned garjan wood frame of section of 50 mm x 25 mm at 600 mm x 600 mm in grid.	sqm	7.804	3098.001	Three Thousand And Ninety-Eight Point Zero Zero One	24176.799	Twenty-Four Thousand One Hundred And Seventy-Six Point Seven Nine Nine	Yes

including grove where necessary, fitted and fixed to wall by plugs, nails, screws etc. maintaining leveled and finished exposed faces including. making holes in wall and mending good the damages, if any during execution of the work, including the provisions of lighting arrangement, also including cost and carriage of all materials, electricity, accessories, labour for installation, scaffolding, screws, nails etc. All complete as per design, approved sample and accepted by the Engineer-in-charge. All sizes of wood are finished. All Garjan wood frames must be protected from termites, cockroach and other insects. Measurement will be taken as per finished surface area. The brick/ RCC surface shall be dry and damp-proof. (Rate is excluding cost of polish/ paint etc. of any type). 12 mm thick BT ply board walling

7	Civil	06.4.5	Supplying, fitting and fixing foreign made polished pocelain/ mirror polished homogeneous floor tiles complying BDS ISO 13006: 2015, water absorption $\leq 0.5\%$, modulus of rupture (MOR) ≥ 35 N/mm ² , irrespective of color &/or design, with 20 mm thick cement sand (F.M. 1.2) mortar	sqm	30.483	1952.001	One Thousand Nine Hundred And Fifty-Two Point Zero Zero One	59502.846	Fifty-Nine Thousand Five Hundred And Two Point Eight Four Six	Yes
---	-------	--------	---	-----	--------	----------	---	-----------	---	-----

			raking out the joints with white cement including cutting and laying the tiles in proper way and finishing with care etc. all complete and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) In ground floor. Polished pocelain/ mirror polished 800 mm x 800 mm floor tiles							
8	Civil	14.15.1	Supplying, fitting, fixing of aluminium sliding fly proof Netting shutter as per the U.S. Architectural Aluminium Manufacturer's Association (AAMA) standard specification and BDS 1879:2014 having 2.0 mm thick outer frame (size 38mm x 38mm), minimum 1.2 mm thick mosquito net shutter frame mesh section (42.2 mm x13.2mm). All aluminium members will be anodized to aluminium bronze/ silver/ss/black colour with a coat not less than 15 microns in thickness or powder coated to any colour with a coat not less than 25 microns in thickness and density of 4 mg per square cm etc. including all accessories like wheel, sealent, rubber, bolts and nuts keeping provision for fitting fiber mesh including labour charge for fitting of accessories, making grooves and mending good damages, carriage, and electricity, all	sqm	8.922	3798.001	Three Thousand Seven Hundred And Ninety-Eight Point Zero Zero One	33885.764	Thirty-Three Thousand Eight Hundred And Eighty-Five Point Seven Six Four	Yes

			complete in all respect as per drawing and accepted by the Engineer-in-charge. Anodized to any colour							
9	Civil	26.29.1	"Supplying, fitting and fixing of best quality country made 12 mm bib cock made from copper or copper alloy, chromium plated. The faucet conforms BDS EN 200:2009. The faucet tap shall be free from any leakage, permeation and other abnormalities. The water hammer value shall be 1.47 Mpa or under. The faucet after it has been operated 100000 times it shall be free from a seat- leakage and shall satisfy the reverse flow preventing performance. The inside and outside surfaces of the faucet shall be smooth and be free from blowholes, fissures, remarkable flows or injurious defects. The chromium plating on the faucet shall be of class 2 grade 1. The final coating should be done with chromium of minimum 0.1 micron. The faucet shall be made leak proof and fixing in position with selected tape etc. , all complete approved and accepted by the Engineer- in-charge. Round headed CP Conceal Bib Cock	each	2.000	1172.001	One Thousand One Hundred And Seventy-Two Point Zero Zero One	2344.002	Two Thousand Three Hundred And Forty-Four Point Zero Zero Two	Yes

			diamond/delux/ deco/orbed/delin/ triple/master/ classic headed or similar head)"							
10	Civil	26.32.2	Supplying, fitting and fixing of best quality CP self closing pillar cock without mixer (SensorType /Push Type) with necessary hardware etc. complete approved and accepted by the Engineer- in- charge. Push Type Self closing pillar cock	each	3.000	1366.001	One Thousand Three Hundred And Sixty- Six Point Zero Zero One	4098.003	Four Thousand And Ninety- Eight Point Zero Zero Three	Yes
11	Civil	26.38.2	Moving type 150 mm CP shower head	each	2.000	2276.001	Two Thousand Two Hundred And Seventy- Six Point Zero Zero One	4552.002	Four Thousand Five Hundred And Fifty- Two Point Zero Zero Two	Yes
12	Civil	26.01.7	"Supplying, fitting and fixing of European type country made best quality glazed porcelain combi closet (two piece), including plastic seat cover with soft closing ,cistern system, water consumption 6 litre, siphon wash down/ siphon jet single or dual flushing system which reduce water consumption, hygienic glaze in toilet bowl ,glaze in inner waste line, round bowl, outlet range 280~305 mm. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a	each	1.000	22075.001	Twenty- Two Thousand And Seventy- Five Point Zero Zero One	22075.001	Twenty- Two Thousand And Seventy- Five Point Zero Zero One	Yes

distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. The fixture should be placed in position preparing the base with cement concrete and with wire mesh or rods if necessary, in all floors including making holes wherever required and mending good the damages and fitting, fixing, finishing, complete with all necessary fittings and connection approved and accepted by the Engineer- in-charge. Approx. 702~ 750x 380~412 mm size, minimum 40.0 kg of weight, Equivalent to COTTO: C118 / RAK: Shino or similar brand"

13	Civil	26.18.1	Supplying, fitting and fixing of best quality double bowl stainless steel sink with heavy type CI or steel brackets, 12 mm dia C.P. chain plug, 40 mm dia C.P. waste, 40 mm dia PVC waste pipe with brass coupling (750 mm length) including making hole in walls and floors and mending good the damages,	each	1.000	8486.001	Eight Thousand Four Hundred And Eighty-Six Point Zero Zero One	8486.001	Eight Thousand Four Hundred And Eighty-Six Point Zero Zero One	Yes
----	-------	---------	--	------	-------	----------	--	----------	--	-----

			complete approved and accepted by the Engineer-in-charge. Approx. 1160 x 500 mm size double bowl with sink tray (Standard)							
14	Civil	12.8.1	Supplying, fitting and fixing of 40mm thick Wood Plastic Composite (WPC) door shutter (minimum inner wall thickness 6mm and hinge side wall thickness 15mm) having door frame section 150mm x 62mm weighing 16.7kg/sqm with 4nos 100mm long, 3mm thick hinge, 1 no round lock, 2nos 150mm long handle, hinged cleats and carrying the same to the site and local carriage etc. All complete in all floors and accepted by the Engineer-in-charge.	each	3.000	17698.001	Seventeen Thousand Six Hundred And Ninety-Eight Point Zero Zero One	53094.003	Fifty-Three Thousand And Ninety-Four Point Zero Zero Three	Yes
15	Civil	26.12.4	"Supplying, fitting and fixing of country made glazed vitreous W/ H wash basin excluding pedestal. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. The mean value of water absorption shall not be greater than 0.5% of the ware when dry.	each	4.000	4448.001	Four Thousand Four Hundred And Forty-Eight Point Zero Zero One	17792.004	Seventeen Thousand Seven Hundred And Ninety-Two Point Zero Zero Four	Yes

When tested with chemical solutions The materials used for making glaze shall not contain lead compound. In case of certain coloring oxides used for making colored glaze, the lead content, if any, shall not exceed 5 percent of the weight of the glaze materials. Appliances shall be clearly and indelibly marked at a prominent place, visible even after the appliances are installed with the following: a) manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. Over Counter: Approx. 560 X 475 mm size, minimum weight 10.0 kg The fixture should be placed in position with heavy type C.I. Brackets. 30 mm dia PVC waste water pipe with brass coupling (not exceeding 750 mm in length), basin waste with chain plug including making holes in walls and floors and fitting with wall, screws and mending good the damages, finishing etc. all complete approved and accepted by the Engineer-in-charge."

16	Civil	1.8.1.5	1C-2x10 sqmm (BYM) cable with 10 sqmm (BYA) ECC wire	meter	17.000	647.001	Six Hundred And Forty-Seven Point Zero	10999.017	Ten Thousand Nine Hundred And	Yes
----	-------	---------	--	-------	--------	---------	--	-----------	-------------------------------	-----

									Nine Point Zero One Seven	
17	Civil	4.12.1.4	GANG SWITCH. Providing & fixing 250 volts. 5 / 6 amps (minimum) concealed type following switch / switch socket Manufactured / Assembled and tested in accordance with IEC / VDE / NEMA / BS / JIS along with relevant BDS IEC standards mounted on required size 18 SWG galvanized plain sheet / PVC board (Self- extinguishing 650 Degree Centigrade) of 76.2 mm (3") depth. All electrical contacts shall be of brass / copper. One gang switch & one 5/10 amps. 2-pin socket combined.	each	4.000	1323.001	One Thousand Three Hundred And Twenty- Three Point Zero Zero One	5292.004	Five Thousand Two Hundred And Ninety- Two Point Zero Zero Four	Yes
18	Civil	21.2.3	"EXHAUST FAN Providing and fixing of following axial flow AC capacitor type wall mounted exhaust fan complete with blade, steel frame standard wall louver shutter, PVC insulated connecting wire etc. complete as required including cutting wall and mending good the damages as per direction of the Engineer. 12"" Exhaust fan plastic body (foreign made accepted / approved by the Engineer)."	each	1.000	1583.001	One Thousand Five Hundred And Eighty- Three Point Zero Zero One	1583.001	One Thousand Five Hundred And Eighty- Three Point Zero Zero One	Yes
							Grand Total:	499789.326	Four Lakh Ninety- Nine Thousand Seven Hundred And Eighty- Nine Point	

<https://www.eprocure.gov.bd/resources/common/ViewBOQFormsLT...>

[illegible]

This Priced Bill of Quantities (BOQ) is Electronically Signed by Mrs. Nargis Kabir on behalf of NADIYA ENTERPRISE

DHAKA WATER SUPPLY & SEWERAGE AUTHORITY

Office of the Executive Engineer
Civil Maintenance Division
Dhaka WASA, Dhaka
6th floor, WASA Bhaban
98 Kazi Nazrul Islam avenue, Dhaka.

Name of the Work: Repair and maintenance works of building Rojonigondha at Duaripara WASA Quarter Compound, Dhaka.

Item No.	Group	PWD 2022	Description of Items of Works	Unit	Quantity	Unit rates or prices	Amount
1	Civil	15.1.1	Minimum 12 mm thick cement sand (F.M. 1:2) plaster (1:4) with fresh cement to both inner-and outer surface of wall, finishing the corner and edges including washing of sand, cleaning the surface, curing at least for 7 days, cost of water, electricity, scaffolding and other charges etc. all complete in all respect as per drawing and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) ground floor.	sqm	125.507	299.001	37,526.719
2	Civil	16.2.1	Interior standard acrylic emulsion paint (plastic or matt finish) of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container; applying to interior wall and ceiling with surface preparation including cleaning drying, making free from dirt, grease, wax, removing all chalked and scaled materials, fungus, mending good the surface defects using sand paper and necessary scaffolding; applying necessary interior sealer of specified brand on prepared surface; then applying necessary interior putty of specified brand for levelling, spot filling, crack filling and cutting by sand paper/zero water paper; finally applying 2 coats of interior emulsion paint spreading by brush/roller/spray & necessary scaffolding etc. upto desired finishing, elapsing specified time for drying or recoating; all complete in all floors and accepted by the Engineer-incharge.	sqm	381.844	258.001	98,516.134
3	Civil	16.3.2	Premium synthetic enamel paint of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container, having high water resistance, high bondability, flexibility property; using specified brand thinner applying to metallic or wooden surface by brass/roller/spray in two coats over single coat anti-corrosive coating including cleaning, drying, making free from dirt, grease, wax, removing all chalked and scaled materials, all complete in all floors and accepted by the Engineer-in-charge.	sqm	100.372	238.001	23,888.636
4	Civil	11.1.2.1	Supplying and making door and window frames (Chowkat) for all floors in/c wall side grove cutting, moulding by CNC machine or any other means with matured seasoned wood of required size including painting two coats of coal tar to the surface in contact with wall, fitting and fixing in position etc. all complete and accepted by the Engineer-in-charge. (All sizes of wood are finished).	cmu	0.150	145620.001	21,843.000

Signature

Signature

Signature

5	Civil	12.1.2.2	Supplying, fitting and fixing of 38 mm thick well matured seasoned (moisture content should be between 12% to 16%) solid wood single leaf door shutter having stile section 100mm x 38mm, top rail section 125mm x 38mm, lock rail section 100mm x 38mm and bottom rail section 225mm x 38mm (made from minimum 250mm wide plank) with 4nos 100mm long, 3mm thick hinge, 12mm dia 250mm long tower bolt, 12mm dia 200mm long socket bolt, 2nos 150mm long handle, hinged cleats and buffer blocks. All complete in all floors and accepted by the Engineer-in-charge. (All sizes of wood are finished)	sqm	8.454	8296.001	70,134.392
6	Civil	18.2.1.2	Supplying, fitting and fixing 12 mm thick burma teak (BT) veneered board/ ply board/ particle board in walling with best quality and well seasoned garjan wood frame of section of 50 mm x 25 mm at 600 mm x 600 mm in grid, including grove where necessary, fitted and fixed to wall by plugs, nails, screws etc. maintaining leveled and finished exposed faces including. making holes in wall and mending good the damages, if any during execution of the work, including the provisions of lighting arrangement, also including cost and carriage of all materials, electricity, accessories, labour for installation, scaffolding, screws, nails etc. All complete as per design, approved sample and accepted by the Engineer-in-charge. All sizes of wood are finished. All Garjan wood frames must be protected from termites, cockroach and other insects. Measurement will be taken as per finished surface area. The brick/ RCC surface shall be dry and damp-proof. (Rate is excluding cost of polish/ paint etc. of any type). 12 mm thick BT ply board walling	sqm	7.804	3098.001	24,176.800
7	Civil	06.4.5	Supplying, fitting and fixing foreign made polished pocelain/ mirror polished homogeneous floor tiles complying BDS ISO 13006: 2015, water absorption $\leq 0.5\%$, modulus of rupture (MOR) ≥ 35 N/mm², irrespective of color &/or design , with 20 mm thick cement sand (F.M. 1.2) mortar (1:4) base and raking out the joints with white cement including cutting and laying the tiles in proper way and finishing with care etc./ all complete and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) In ground floor. Polished pocelain/ mirror polished 800 mm x 800 mm floor tiles	sqm	30.483	1952.001	59,502.846
8		14.15.1	Supplying, fitting, fixing of aluminium sliding fly proof Netting shutter as per the U.S. Architectural Aluminium Manufacturer's Association (AAMA) standard specification and BDS 1879:2014 having 2.0 mm thick outer frame (size 38mm x 38mm), minimum 1.2 mm thick mosquito net shutter frame mesh section (42.2 mm x13.2mm). All aluminium members will be anodized to aluminium bronze/silver/ss/black colour with a coat not less than 15 microns in thickness or powder coated to any colour with a coat not less than 25 microns in thickness and density of 4 mg per square cm etc. including all accessories like wheel, sealent, rubber, bolts and nuts keeping provision for fitting fiber mesh including labour charge for fitting of accessories, making grooves and mending good damages, carriage, and electricity, all complete in all respect as per drawing and accepted by the Engineer-in-charge. Anodized to any colour	sqm	8.922	3798.001	33,885.765

Arif

Rahman

Faraz

9	Civil	26.29.1	Supplying, fitting and fixing of best quality country made 12 mm bib cock made from copper or copper alloy, chromium plated. The faucet conforms BDS EN 200:2009. The faucet tap shall be free from any leakage, permeation and other abnormalities. The water hammer value shall be 1.47 Mpa or under. The faucet after it has been operated 100000 times it shall be free from a seat- leakage and shall satisfy the reverse flow preventing performance. The inside and outside surfaces of the faucet shall be smooth and be free from blowholes, fissures, remarkable flows or injurious defects. The chromium plating on the faucet shall be of class 2 grade 1. The final coating should be done with chromium of minimum 0.1 micron. The faucet shall be made leak proof and fixing in position with selected tape etc. , all complete approved and accepted by the Engineer- in- charge. Round headed CP Conceal Bib Cock short body (Essco/coaster/star/diamond/delux/deco/orbed/delin/triple/master/classic headed or similar head)	each	2.00	1172.001	2,344.002
10	Civil	26.32.2	Supplying, fitting and fixing of best quality CP self closing pillar cock without mixer (SensorType /Push Type) with necessary hardware etc. complete approved and accepted by the Engineer- in- charge. Push Type Self closing pillar cock	each	3.00	1366.001	4,098.003
11		26.38.2	Moving type 150 mm CP shower head	each	2.00	2276.001	4,552.002
12		26.01.7	Supplying, fitting and fixing of European type country made best quality glazed porcelain combi closet (two piece) , including plastic seat cover with soft closing ,cistern system, water consumption 6 litre, siphon wash down/siphon jet single or dual flushing system which reduce water consumption, hygienic glaze in toilet bowl ,glaze in inner waste line, round bowl, outlet range 280~305 mm. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. The fixture should be placed in position preparing the base with cement concrete and with wire mesh or rods if necessary, in all floors including making holes wherever required and mending good the damages and fitting, fixing, finishing, complete with all necessary fittings and connection approved and accepted by the Engineer- in- charge. Approx. 702~ 750x 380~412 mm size, minimum 40.0 kg of weight, Equivalent to COTTO: C118 / RAK: Shino or similar brand	each	1.00	22075.001	22,075.001
13		26.18.1	Supplying, fitting and fixing of best quality double bowl stainless steel sink with heavy type CI or steel brackets, 12 mm dia C.P. chain plug, 40 mm dia C.P. waste, 40 mm dia PVC waste pipe with brass coupling (750 mm length) including making hole in walls and floors and mending good the damages, finishing etc. all complete approved and accepted by the Engineer-in-charge. Approx. 1160 x 500 mm size double bowl with sink tray (Standard)	each	1.00	8486.001	8,486.001

Signature

Signature

Signature

14		12.8.1	Supplying, fitting and fixing of 40mm thick Wood Plastic Composite (WPC) door shutter (minimum inner wall thickness 6mm and hinge side wall thickness 15mm) having door frame section 150mm x 62mm weighing 16.7kg/sqm with 4nos 100mm long, 3mm thick hinge, 1 no round lock, 2nos 150mm long handle, hinged cleats and carrying the same to the site and local carriage etc. All complete in all floors and accepted by the Engineer-in-charge.	each	3.000	17698.001	53,094.003
15		26.12.4	Supplying, fitting and fixing of country made glazed vitreous W/H wash basin excluding pedestal. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. The mean value of water absorption shall not be greater than 0.5% of the ware when dry. When tested with chemical solutions The materials used for making glaze shall not contain lead compound. In case of certain coloring oxides used for making colored glaze, the lead content, if any, shall not exceed 5 percent of the weight of the glaze materials. Appliances shall be clearly and indelibly marked at a prominent place, visible even after the appliances are installed with the following: a) manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. Over Counter: Approx. 560 X 475 mm size, minimum weight 10.0 kg The fixture should be placed in position with heavy type C.I. Brackets. 30 mm dia PVC waste water pipe with brass coupling (not exceeding 750 mm in length), basin waste with chain plug including making holes in walls and floors and fitting with wall, screws and mending good the damages, finishing etc. all complete approved and accepted by the Engineer-in-charge.	nos	4.00	4448.001	17,792.004
16	Electrical	1.8.1.5	1C-2x10 sqmm (BYM) cable with 10 sqmm (BYA) ECC wire	meter	17.00	647.001	10,999.017
17	Electrical	4.12.1.4	GANG SWITCH. Providing & fixing 250 volts. 5 / 6 amps (minimum) concealed type following switch / switch socket Manufactured / Assembled and tested in accordance with IEC / VDE / NEMA / BS / JIS along with relevant BDS IEC standards mounted on required size 18 SWG galvanized plain sheet / PVC board (Self-extinguishing 650 Degree Centigrade) of 76.2 mm (3") depth. All electrical contacts shall be of brass / copper. One gang switch & one 5/10 amps. 2-pin socket combined.	each	4.00	1,323.00	5,292.004
18	Civil	21.2.3	EXHAUST FAN Providing and fixing of following axial flow AC capacitor type wall mounted exhaust fan complete with blade, steel frame standard wall louver shutter, PVC insulated connecting wire etc. complete as required including cutting wall and mending good the damages as per direction of the Engineer. 12" Exhaust fan plastic body (foreign made accepted / approved by the Engineer).	each	1.00	1583.001	1,583.001
						Total:	499,789.330

499,789

In word: (Four lakh ninety nine thousand seven hundred eighty nine) taka only

Signature
১০/১০/২০
রাজিয়া সুলতানা
উপ-সহকারী প্রকৌশলী
সি এম বিভাগ
ঢাকা ওয়াশা।

Signature
১৫.১০.২৫
রাহাত উন নবী
সহকারী প্রকৌশলী
সি এম বিভাগ

Signature
১৫/১০/২৫
মুজা সাহা
নির্বাহী প্রকৌশলী
সিএম বিভাগ