

M/S SHARIF TRADERS

Tenderer's Quoted Price

Tenderer's Quoted Price

Total Estimated Cost (BDT)	Percentage (-5% to +5%)	Offered Amount (in figures) (BDT)	Offered Amount (in words) (BDT)
499929.000	-5.000	474932.550	Four Lakh Seventy-Four Thousand Nine Hundred And Thirty-Two Point Five Five
	Grand Total:	474932.550	Four Lakh Seventy-Four Thousand Nine Hundred And Thirty-Two Point Five Five

This Tenderer's Quoted Price is Electronically Signed by Mr. Md Uddin on behalf of M/S SHARIF TRADERS

M/S SHARIF TRADERS

Priced Bill of Quantities (BOQ)

Unit Rate Basis

Estimate by the Procuring Entity

Item no.	Group	Item Code (if any)	Description of Item	Unit	Quantity	Unit rates or prices (in figures) (BDT)	Unit rates or prices (in words) (BDT)	Amount (in figure) (BDT)	Amount (in words) (BDT)	Select 'YES' to see the Grand Total
1	civil	15.1.1	Minimum 12 mm thick cement sand (F.M. 1:2) plaster (1:4) with fresh cement to both inner-and outer surface of wall, finishing the corner and edges including washing of sand, cleaning the surface, curing at least for 7 days, cost of water, electricity, scaffolding and other charges etc. all complete in all respect as per drawing and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) ground floor.	sqm	235.409	299.001	Two Hundred And Ninety-Nine Point Zero Zero One	70387.526	Seventy Thousand Three Hundred And Eighty-Seven Point Five Two Six	Yes
2	civil	16.2.1	Interior standard acrylic emulsion paint (plastic or matt finish) of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container; applying to interior wall and ceiling with surface preparation including cleaning drying, making free from dirt, grease, wax, removing all chalked and scaled materials,	sqm	388.333	258.001	Two Hundred And Fifty-Eight Point Zero Zero One	100190.302	One Lakh One Hundred And Ninety Point Three Zero Two	Yes

			fungus, mending good the surface defects using sand paper and necessary scaffolding; applying necessary interior sealer of specified brand on prepared surface; then applying necessary interior putty of specified brand for levelling, spot filling, crack filling and cutting by sand paper/ zero water paper; finally applying 2 coats of interior emulsion paint spreading by brush/roller/spray & necessary scaffolding etc. upto desired finishing, elapsing specified time for drying or recoating; all complete in all floors and accepted by the Engineer-incharge.							
3	civil	16.3.2	Premium synthetic enamel paint of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container, having high water resistance, high bondability, flexibility property; using specified brand thinner applying to metallic or wooden surface by brass/roller/ spray in two coats over single coat anti-corrosive coating including cleaning, drying, making free from dirt, grease, wax, removing all chalked and scaled materials, all complete in all	sqm	70.260	238.001	Two Hundred And Thirty-Eight Point Zero Zero One	16721.950	Sixteen Thousand Seven Hundred And Twenty-One Point Nine Five	Yes

			accepted by the Engineer-in-charge.							
4	civil	11.1.2.1	Supplying and making door and window frames (Chowkat) for all floors in/c wall side grove cutting, moulding by CNC machine or any other means with matured seasoned wood of required size including painting two coats of coal tar to the surface in contact with wall, fitting and fixing in position etc. all complete and accepted by the Engineer-in-charge. (All sizes of wood are finished).	cum	0.150	145620.001	One Lakh Forty-Five Thousand Six Hundred And Twenty Point Zero Zero One	21843.000	Twenty-One Thousand Eight Hundred And Forty-Three	Yes
5	civil	12.1.2.2	"Supplying, fitting and fixing of 38 mm thick well matured seasoned (moisture content should be between 12% to 16%) solid wood single leaf door shutter having stile section 100mm x 38mm, top rail section 125mm x 38mm, lock rail section 100mm x 38mm and bottom rail section 225mm x 38mm (made from minimum 250mm wide plank) with 4nos 100mm long, 3mm thick hinge, 12mm dia 250mm long tower bolt, 12mm dia 200mm long socket bolt, 2nos 150mm long handle, hinged cleats and buffer blocks. All complete in all floors and accepted by the Engineer-in-charge. (All sizes of wood are finished)"	sqm	12.671	8296.001	Eight Thousand Two Hundred And Ninety-Six Point Zero Zero One	105118.628	One Lakh Five Thousand One Hundred And Eighteen Point Six Two Eight	Yes

6	civil	06.4.5	"Supplying, fitting and fixing foreign made polished pocelain/ mirror polished homogeneous floor tiles complying BDS ISO 13006: 2015, water absorption ≤ 0.5%, modulus of rupture (MOR) ≥ 35 N/mm ² , irrespective of color &/or design, with 20 mm thick cement sand (F.M. 1.2) mortar (1:4) base and raking out the joints with white cement including cutting and laying the tiles in proper way and finishing with care etc. all complete and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) In ground floor. Polished pocelain/ mirror polished 800 mm x 800 mm floor tiles	sqm	60.967	1952.001	One Thousand Nine Hundred And Fifty-Two Point Zero Zero One	119007.644	One Lakh Nineteen Thousand And Seven Point Six Four Four	Yes
7	civil	32.22	Renewing of 5 mm glass panes including supply of glass	sqm	6.691	1348.001	One Thousand Three Hundred And Forty-Eight Point Zero Zero One	9019.474	Nine Thousand And Nineteen Point Four Seven Four	Yes
8	civil	26.29.1	"Supplying, fitting and fixing of best quality country made 12 mm bib cock made from copper or copper alloy, chromium plated. The faucet conforms BDS EN 200:2009. The faucet tap shall be free from any leakage, permeation and other abnormalities. The water hammer value shall be 1.47 Mpa or less. The faucet	each	6.000	1172.001	One Thousand One Hundred And Seventy-Two Point Zero Zero One	7032.006	Seven Thousand And Thirty-Two Point Zero Zero Six	Yes

			after it has been operated 100000 times it shall be free from a seat-leakage and shall satisfy the reverse flow preventing performance. The inside and outside surfaces of the faucet shall be smooth and be free from blowholes, fissures, remarkable flows or injurious defects. The chromium plating on the faucet shall be of class 2 grade 1. The final coating should be done with chromium of minimum 0.1 micron. The faucet shall be made leak proof and fixing in position with selected tape etc. , all complete approved and accepted by the Engineer- in-charge. Round headed CP Conceal Bib Cock short body (Essco/ /coaster/star/ diamond/delux/ deco/orbed/delin/ triple/master/ classic headed or similar head)"							
9	civil	26.32.2	Supplying, fitting and fixing of best quality CP self closing pillar cock without mixer (SensorType / Push Type) with necessary hardware etc. complete approved and accepted by the Engineer- in-charge. Push Type Self closing pillar cock	each	4.000	1366.001	One Thousand Three Hundred And Sixty-Six Point Zero Zero One	5464.004	Five Thousand Four Hundred And Sixty-Four Point Zero Zero Four	Yes
10	civil	26.12.4	"Supplying, fitting and fixing of country made glazed vitreous W/ H wash basin	nos	4.000	4448.001	Four Thousand Four Hundred And	17792.004	Seventeen Thousand Seven Hundred And	Yes

excluding pedestal. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. The mean value of water absorption shall not be greater than 0.5% of the ware when dry. When tested with chemical solutions The materials used for making glaze shall not contain lead compound. In case of certain coloring oxides used for making colored glaze, the lead content, if any, shall not exceed 5 percent of the weight of the glaze materials. Appliances shall be clearly and indelibly marked at a prominent place, visible even after the appliances are installed with the following: a) manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. Over Counter: Approx. 560 X 475

Forty-
Eight
Point
Zero Zero
One

Ninety-
Two Point
Zero Zero
Four

			weight 10.0 kg The fixure should be placed in position with heavy type C.I. Brackets. 30 mm dia PVC waste water pipe with brass coupling (not exceeding 750 mm in length), basin waste with chain plug including making holes in walls and floors and fitting with wall, screws and mending good the damages, finishing etc. all complete approved and accepted by the Engineer-in-charge."							
11	Electrical	1.8.1.5	1C-2x10 sqmm (BYM) cable with 10 sqmm (BYA) ECC wire	meter	17.000	647.001	Six Hundred And Forty-Seven Point Zero Zero One	10999.017	Ten Thousand Nine Hundred And Ninety-Nine Point Zero One Seven	Yes
12	Electrical	4.12.1.4	GANG SWITCH. Providing & fixing 250 volts. 5 / 6 amps (minimum) concealed type following switch / switch socket Manufactured / Assembled and tested in accordance with IEC / VDE / NEMA / BS / JIS along with relevant BDS IEC standards mounted on required size 18 SWG galvanized plain sheet / PVC board (Self-extinguishing 650 Degree Centigrade) of 76.2 mm (3") depth. All electrical contacts shall be of brass / copper. One gang switch & one 5/10 amps. 2-pin socket combined.	each	6.000	1323.000	One Thousand Three Hundred And Twenty-Three	7938.000	Seven Thousand Nine Hundred And Thirty-Eight	Yes

13	civil	26.43.2	Supplying different inside dia best quality uPVC soil, waste and ventilation pipe having specific gravity 1.35 - 1.45, wall thickness 2.5 mm - 3.0 mm, and other physical, chemical, thermal, fire resistivity properties etc. as per BSTI approved manufacturer standards or ASTM, BS/ISO/IS standards fitting and fixing in position with sockets, bends, of uPVC Pipe with all accessories such as Round grating / domed roof grating bands, sockets etc. approved and accepted by the Engineer- in-charge. 100 mm inside dia wall thickness 3.4- 4.0 mm	meter	7.000	881.001	Eight Hundred And Eighty-One Point Zero Zero One	6167.007	Six Thousand One Hundred And Sixty-Seven Point Zero Zero Seven	Yes
14	civil	26.51.5	Supplying, fitting and fixing of G.I. Union with sealant etc. complete in all respects approved and accepted by the Engineer- in-charge. 40 mm dia G.I. Union	each	2.000	491.001	Four Hundred And Ninety-One Point Zero Zero One	982.002	Nine Hundred And Eighty-Two Point Zero Zero Two	Yes
15	civil	26.52	Supplying, fitting and fixing of best quality G.I. gate valve with sealant etc. complete approved and accepted by the Engineer- in-charge. 20 mm brass gate valve	each	2.000	633.000	Six Hundred And Thirty-Three	1266.000	One Thousand Two Hundred And Sixty-Six	Yes
							Grand Total:	499928.564	Four Lakh Ninety-Nine Thousand Nine Hundred And Twenty-Eight Point Five Six Four	

Priced Bill of Quantities (BOQ) is Electronically Signed by Mr. Md Uddin on behalf of M/S SHARIF TRADERS

DHAKA WATER SUPPLY & SEWERAGE AUTHORITY

Office of the Executive Engineer
Civil Maintenance Division
Dhaka WASA, Dhaka
6th floor, WASA Bhaban
98 Kazi Nazrul Islam avnue, Dhaka.

Name of the Work: Repair and maintenance works of building (Korobi & Shapla) at Duaripara WASA quarter compound, Dhaka.

Item No.	Group	PWD 2022	Description of Items of Works	Unit	Quantity	Unit rates or prices	Amount
1	Civil	15.1.1	Minimum 12 mm thick cement sand (F.M. 1.2) plaster (1:4) with fresh cement to both inner-and outer surface of wall, finishing the corner and edges including washing of sand, cleaning the surface, curing at least for 7 days, cost of water, electricity, scaffolding and other charges etc. all complete in all respect as per drawing and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) ground floor.	sqm	235.409	299.001	70,387.526
2	Civil	16.2.1	Interior standard acrylic emulsion paint (plastic or matt finish) of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container; applying to interior wall and ceiling with surface preparation including cleaning drying, making free from dirt, grease, wax, removing all chalked and scaled materials, fungus, mending good the surface defects using sand paper and necessary scaffolding; applying necessary interior sealer of specified brand on prepared surface; then applying necessary interior putty of specified brand for levelling, spot filling, crack filling and cutting by sand paper/zero water paper; finally applying 2 coats of interior emulsion paint spreading by brush/roller/spray & necessary scaffolding etc. upto desired finishing, elapsing specified time for drying or recoating; all complete in all floors and accepted by the Engineer-in-charge.	sqm	388.333	258.001	100,190.302
3	Civil	16.3.2	Premium synthetic enamel paint of approved best quality and colour delivered from authorized local agent of the manufacturer in a sealed container, having high water resistance, high bondability, flexibility property; using specified brand thinner applying to metallic or wooden surface by brass/roller/spray in two coats over single coat anti-corrosive coating including cleaning, drying, making free from dirt, grease, wax, removing all chalked and scaled materials, all complete in all floors and accepted by the Engineer-in-charge.	sqm	70.260	238.001	16,721.950
4	Civil	11.1.2.1	Supplying and making door and window frames (Chowkat) for all floors in/c wall side grove cutting, moulding by CNC machine or any other means with matured seasoned wood of required size including painting two coats of coal tar to the surface in contact with wall, fitting and fixing in position etc. all complete and accepted by the Engineer-in-charge. (All sizes of wood are finished).	cmu	0.150	145620.001	21,843.000

Amber

Rahat

Shah

5	Civil	12.1.2.2	Supplying, fitting and fixing of 38 mm thick well matured seasoned (moisture content should be between 12% to 16%) solid wood single leaf door shutter having stile section 100mm x 38mm, top rail section 125mm x 38mm, lock rail section 100mm x 38mm and bottom rail section 225mm x 38mm (made from minimum 250mm wide plank) with 4nos 100mm long, 3mm thick hinge, 12mm dia 250mm long tower bolt, 12mm dia 200mm long socket bolt, 2nos 150mm long handle, hinged cleats and buffer blocks. All complete in all floors and accepted by the Engineer-in-charge. (All sizes of wood are finished)	sqm	12.671	8296.001	105,118.629
6	Civil	06.4.5	Supplying, fitting and fixing foreign made polished pocelain/ mirror polished homogeneous floor tiles complying BDS ISO 13006: 2015, water absorption $\leq 0.5\%$, modulus of rupture (MOR) ≥ 35 N/mm², irrespective of color &/or design , with 20 mm thick cement sand (F.M. 1.2) mortar (1:4) base and raking out the joints with white cement including cutting and laying the tiles in proper way and finishing with care etc. all complete and accepted by the Engineer-in-charge. (Cement: CEM-II/B-M) In ground floor. Polished pocelain/ mirror polished 800 mm x 800 mm floor tiles	sqm	60.967	1952.001	119,007.645
7		32.22	Renewing of 5 mm glass panes including supply of glass	sqm	6.691	1,348.001	9,019.475
8	Civil	26.29.1	Supplying, fitting and fixing of best quality country made 12 mm bib cock made from copper or copper alloy, chromium plated. The faucet conforms BDS EN 200:2009. The faucet tap shall be free from any leakage, permeation and other abnormalities. The water hammer value shall be 1.47 Mpa or under. The faucet after it has been operated 100000 times it shall be free from a seat- leakage and shall satisfy the reverse flow preventing performance. The inside and outside surfaces of the faucet shall be smooth and be free from blowholes, fissures, remarkable flows or injurious defects. The chromium plating on the faucet shall be of class 2 grade 1. The final coating should be done with chromium of minimum 0.1 micron. The faucet shall be made leak proof and fixing in position with selected tape etc. , all complete approved and accepted by the Engineer- in- charge. Round headed CP Conceal Bib Cock short body (Essco/coaster/star/diamond/delux/deco/orbed/delin/triple/master/classic headed or similar head)	each	6.00	1172.001	7,032.006
9	Civil	26.32.2	Supplying, fitting and fixing of best quality CP self closing pillar cock without mixer (SensorType /Push Type) with necessary hardware etc. complete approved and accepted by the Engineer- in- charge. Push Type Self closing pillar cock	each	4.00	1366.001	5,464.004

Infra

Rahatun

King

10		26.12.4	Supplying, fitting and fixing of country made glazed vitreous W/H wash basin excluding pedestal. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The minimum thickness of body at any section shall be 5 mm. When assembled together and when examined from a distance of 60 cm, the outer surface shall not show to the unaided eye, blemishes or defects in excess of those listed in BDS standard. The mean value of water absorption shall not be greater than 0.5% of the ware when dry. When tested with chemical solutions The materials used for making glaze shall not contain lead compound. In case of certain coloring oxides used for making colored glaze, the lead content, if any, shall not exceed 5 percent of the weight of the glaze materials. Appliances shall be clearly and indelibly marked at a prominent place, visible even after the appliances are installed with the following: a) manufacturer's name and/or registered trademark, b) the number of Bangladesh standard and c) country of origin. Each product shall also be marked with the BSTI Certification Mark. Over Counter: Approx. 560 X 475 mm size, minimum weight 10.0 kg The fixture should be placed in position with heavy type C.I. Brackets. 30 mm dia PVC waste water pipe with brass coupling (not exceeding 750 mm in length), basin waste with chain plug including making holes in walls and floors and fitting with wall, screws and mending good the damages, finishing etc. all complete approved and accepted by the Engineer-in-charge.	nos	4.00	4448.001	17,792.004
11	Electrical	1.8.1.5	1C-2x10 sqmm (BYM) cable with 10 sqmm (BYA) ECC wire	meter	17.00	647.001	10,999.017
12	Electrical	4.12.1.4	GANG SWITCH. Providing & fixing 250 volts. 5 / 6 amps (minimum) concealed type following switch / switch socket Manufactured / Assembled and tested in accordance with IEC / VDE / NEMA / BS / JIS along with relevant BDS IEC standards mounted on required size 18 SWG galvanized plain sheet / PVC board (Self-extinguishing 650 Degree Centigrade) of 76.2 mm (3") depth. All electrical contacts shall be of brass / copper. One gang switch & one 5/10 amps. 2-pin socket combined.	each	6.00	1,323.00	7,938.006
13	Civil	26.43.2	Supplying different inside dia best quality uPVC soil, waste and ventilation pipe having specific gravity 1.35 - 1.45, wall thickness 2.5 mm - 3.0 mm, and other physical, chemical, thermal, fire resistivity properties etc. as per BSTI approved manufacturer standards or ASTM, BS/ISO/IS standards fitting and fixing in position with sockets, bends, of uPVC Pipe with all accessories such as Round grating /domed roof grating bands, sockets etc. approved and accepted by the Engineer- in- charge. 100 mm inside dia wall thickness 3.4- 4.0 mm	meter	7.00	881.001	6,167.007


M. J. K.

Rahatun

Sana

14	Civil	26.51.5	Supplying, fitting and fixing of G.I. Union with sealant etc. complete in all respects approved and accepted by the Engineer- in- charge. 40 mm dia G.I. Union	each	2.00	491.001	982.002
15	Civil	26.52	Supplying, fitting and fixing of best quality G.I. gate valve with sealant etc. complete approved and accepted by the Engineer- in- charge. 20 mm brass gate valve	each	2.00	633.00	1,266.002
						Total:	499,928.575
						Say	499,929
In word: (Four lac ninty nine thousand nine hundred twenty nine) taka only							


 ১৯/০১/২৬
 রাজিয়া সুলতানা
 উপ-সহকারী প্রকৌশলী
 সি এম বিভাগ
 ঢাকা ওয়াশা।


 19.01.26
 রাহাত উন নবি
 সহকারী প্রকৌশলী
 সি এম বিভাগ
 ঢাকা ওয়াশা।


 ১৯/০১/২৬
 মুজিব সাহা
 নির্বাহী প্রকৌশলী
 সিএম বিভাগ
 ঢাকা ওয়াশা।