

S.S. Enterprise**Price and Delivery Schedule for Goods (Form e-PG2-2A)**

Price and Delivery Schedule for Goods

Item No.	Description of Item	Measurement Unit	Quantity	Point of Delivery	Delivery Period (in days)	Country of Origin	Unit Price in Figure (BDT)	Unit Price in Words (BDT)	Total Price in Figure (BDT)	Total Price in Words (BDT)
1	Supply and Refilling of ABCE Dry chemical extinguisher powder stored pressure for a fire extinguisher as per sample accepted/approved by the engineer. Brand: Fire control, Country of origin: India.	Kg	408.000	PSTP Divisional store	60	India	260.001	Two Hundred and Sixty point Zero Zero One	106080.408	One Lakh Six Thousand AND Eighty point Four Zero Eight
2	Supply and Refilling of CO2 type extinguisher powder stored pressure for a fire extinguisher as per sample accepted/approved by the engineer. Brand: Fire control, Country of origin: India.	Kg	408.000	PSTP Divisional store	60	India	250.001	Two Hundred and Fifty point Zero Zero One	102000.408	One Lakh Two Thousand point Four Zero Eight
3	Providing & fixing of the following parts of fire extinguisher as per sample accepted/approved by the engineer. Trigger Brand: Fire control, Country of origin: India.	each	10.000	PSTP Divisional store	60	India	160.001	One Hundred and Sixty point Zero Zero One	1600.010	One Thousand Six Hundred point Zero One
4	Providing & fixing of the following parts of fire extinguisher as per sample accepted/approved by the engineer. Hose Pipe. Brand: Fire control, Country of origin: India.	each	10.000	PSTP Divisional store	60	India	300.001	Three Hundred point Zero Zero One	3000.010	Three Thousand point Zero One
5	Supply of wheel Shapeguard (as per existing size and sample) to complete the work as per direction of the Engineer.	each	32.000	PSTP Divisional store	60	BD	1600.001	One Thousand Six Hundred point Zero Zero One	51200.032	Fifty-One Thousand Two Hundred point Zero

										Three Two
6	Supply of Nut/bolt, (As per existing size and sample) to complete as per direction of the Engineer.	each	32.000	PSTP Divisional store	60	BD	140.001	One Hundred and Forty point Zero Zero One	4480.032	Four Thousand Four Hundred and Eighty point Zero Three Two
7	"ADDRESSABLE TYPE PHOTOELECTRIC SMOKE DETECTOR Supply & installation of addressable type photoelectric / Optical smoke The detector shall be self-restoring: detectors do not require resetting or readjustment after actuation to restore normal operation. No special tools shall be required to remove head once it has been connected with base. Removal of the detector head shall cause a trouble signal at the control unit. Except false ceiling, detector base shall be fixed with gang box in any other ceiling as per manufacturer instruction. In alarm condition, the sensor LED shall be on steady or have Bicolor (green/red) status LIFE Each sensor shall be scanned by the Control Unit for its type identification to prevent inadvertent substitution of another sensor type. Upon detection of a wrong / unprogrammed device, the control unit shall operate with the installed device at the default alarm settings for that	each	10.000	PSTP Divisional store	60	China	6000.001	Six Thousand point Zero Zero One	60000.010	Sixty Thousand point Zero One

	sensor but shall indicate a unprogrammed device trouble condition. Detector shall have listed Spacing Capacitance of 10 Ohm. Detector shall have at least Two level of fire detector warning. Detector shall have non volatile memory to store the data of Sensitivity values, troubles, etc. Detector having a unique identification shall communicate status to the FACP. Detector shall have at least two sensitivity settings. Removal of the sensor head for cleaning shall not require the setting of addresses. Operating ambient temperature range 45°C (Minimum) shall be minimum: 0°C to 45 deg C (Minimum) Shall be suitable for humidity range: 10% to 95% RH Housing color shall be Frost White or equivalent. Smoke sensor ambient ratings : Air velocity (Minimum) 0-2000 fpm Approvals : UL listed / FM approved"									
8	Providing & fixing of the following parts of fire extinguisher as per sample accepted/approved by the engineer. Nipple with nozzle. Brand: Fire control, Country of origin: India.	each	10.000	PSTP Divisional store	60	India	126.001	One Hundred and Twenty-Six point Zero Zero One	1260.010	One Thousand Two Hundred and Sixty point Zero One
9	Supply of gasket having size inner dia-12", outer dia-16" or any size thickness-1mm, (As per existing size and sample) to complete as per direction of the Engineer.	each	150.000	PSTP Divisional store	60	BD	900.001	Nine Hundred point Zero Zero One	135000.150	One Lakh Thirty-Five Thousand point One Five

10	Supply of Wood Handle Steel Brush for Cleaning Deburring Rust And Oxide Removal Paint Removal And Surface Preparation And Finishing Harden Brand	each	30.000	PSTP Divisional store	60	BD	500.001	Five Hundred point Zero Zero One	15000.030	Fifteen Thousand point Zero Three
11	ADDRESSABLE NOTIFICATION DEVICE (HORN WITH STROBE): Supply & installation of addressable type audible horn with strobe for notification purpose shall contain an electronic module and a selectable address setting. The device shall be suitable to program the high / low setting of the audible (horn) appliance. The horn shall be red color with / without Fire lettering Addressable horn shall be UL listed / FM approved . The horn shall be suitable to produce sound pressure level of 99 dBA @ 24VDC at low level as per NFPA Standard. The horn shall suitable for mount directly to a standard single gang, double gang or 4, square electrical box. without the use of special adapter or trim rings. Shall have suitable operating ambient temperature range : 0o to 45oC (Minimum) Humidity range: Minimum 93% RH at 100°F (38°C) Approvals : LUL-listed / FM approved. The Strobc shall be selectable at 15,30,75, or 110 cd	each	5.000	PSTP Divisional store	60	China	6000.001	Six Thousand point Zero Zero One	30000.005	Thirty Thousand point Zero Zero Five

12	Supply of Grease, Model: Multiple, Temperature: High Temperature usage qualified Brand: SKF/Equvelend.	Kg	25.000	PSTP Divisional store	60	China	7890.001	Seven Thousand Eight Hundred and Ninety point Zero Zero One	197250.025	One Lakh Ninety-Seven Thousand Two Hundred and Fifty point Zero Two Five
13	Supplying and fitting-fixing of wheel outer side rubber molding having size inner dia-17", outer dia-20", thickness-1.5", width-4" or (As per existing size and sample) to primary sedimentation tank 1,2,3 & 4 duly painted with two coats of superior quality paint over two prime coats of red oxide to main ms wheel etc. to complete as per direction of the Engineer.	each	16.000	PSTP Divisional store	60	BD	47420.001	Forty-Seven Thousand Four Hundred and Twenty point Zero Zero One	758720.016	Seven Lakh Fifty-Eight Thousand Seven Hundred and Twenty point Zero One Six
14	Supply of Hand DA (Big size) with wooden hendel.	each	100.000	PSTP Divisional store	60	BD	1460.001	One Thousand Four Hundred and Sixty point Zero Zero One	146000.100	One Lakh Forty-Six Thousand point One
15	Supplying of Synthetic enamel paint Colour: Blue, Berger or equivalent	Liter	292.000	PSTP Divisional store	60	BD	948.001	Nine Hundred and Forty-Eight point Zero Zero One	276816.292	Two Lakh Seventy-Six Thousand Eight Hundred and Sixteen point Two Nine Two
16	2.5 Inch Stainless Steel scrapper Wall Paint Putty scrapper	each	100.000	PSTP Divisional store	60	BD	370.001	Three Hundred and Seventy point Zero Zero One	37000.100	Thirty-Seven Thousand point One
17	ADDRISSABLE MULTI DETECTOR / MULTI SENSORS: Supply & installation of addressable multi-sensors, shall include with photoelcctric /	each	5.000	PSTP Divisional store	60	China	7740.001	Seven Thousand Seven Hundred and Forty point Zero Zero One	38700.005	Thirty-Eight Thousand Seven Hundred point Zero Zero Five

Optical smoke sensing and heat sensing technologies complete with standard base. An alarm shall be determined by either smoke detection, with selectable sensitivity) or heat detection. Selectable as fixed temperature or fixed with selectable rate-of-rise; or based on an analysis of the combination of smoke and heat activity as per NFPA 72. The detector shall be self-restoring: detectors do not require resetting or readjustment after actuation to restore normal operation. No special tools shall be required to remove head once it has been connected with base. Removal of the detector head shall cause a trouble signal at the control unit. Except false ceiling, detector base shall be fixed with gang box or any other ceiling as per manufacturer instruction. In alarm condition, the sensor LED shall be on steady or have Bicolor (green/red) status LED. Each sensor shall be scanned by the Control Unit for its type identification to prevent inadvertent substitution of another sensor type. Upon detection of a wrong / unprogrammed device, the control unit shall operate with the installed device at the default alarm settings for that

	sensor but shall indicate a unprogrammed device trouble condition. Detector shall have at least Two level ordinary detector warning. Detector Shall have non volatile memory to store the data of Sensitivity value troubles etc.									
18	Supply of ball bearing (as per existing size and sample) to complete the work as per direction of the Engineer.	each	11.000	PSTP Divisional store	60	China	27000.001	Twenty-Seven Thousand point Zero Zero One	297000.011	Two Lakh Ninety-Seven Thousand point Zero One One
19	3 Inch Paint Brush Lion Brush Wall Painting Tool	each	120.000	PSTP Divisional store	60	BD	352.001	Three Hundred and Fifty-Two point Zero Zero One	42240.120	Forty-Two Thousand Two Hundred and Forty point One Two
20	120 Series Paper	each	120.000	PSTP Divisional store	60	BD	152.001	One Hundred and Fifty-Two point Zero Zero One	18240.120	Eighteen Thousand Two Hundred and Forty point One Two
21	Supply of Hand kachi with wooden handle.	each	10.000	PSTP Divisional store	60	BD	310.001	Three Hundred and Ten point Zero Zero One	3100.010	Three Thousand One Hundred point Zero One
22	"ADDRESSABLE MANUAL PULL STATION (MPS): Supply & installation of addressable type manual call station of red color. Station will mechanically latch upon operation and remain so until manually reset by opening with a key common with the control units. Shall be with compact construction, suitable to electronics module enclosure minimizes dust infiltration. Allows mounting in standard electrical boxes. Screw terminals for wiring	each	2.000	PSTP Divisional store	60	China	9250.001	Nine Thousand Two Hundred and Fifty point Zero Zero One	18500.002	Eighteen Thousand Five Hundred point Zero Zero Two

connections.
 Activation of the
 MPS will required
 a firm do\$ward
 pull to actilate the
 alarm switch. Ihe
 pull lever latches
 into the alarm
 position and
 remains extended
 out ofthe housing
 to providc a visible
 indication.
 Operating ambient
 temperature range
 shall bc : 0. to
 4soc(Minimum)
 Humidity range:
 93% RH(minimum)
 al t00""F (.18""C)
 Housing color shall
 be red with white
 raised lcttering.
 Ilousing and pull
 lever shall be
 made with lcxan
 polycarbonate or
 equal. 'fhe MPS
 shall bc semi-flash
 / surface mounr
 lype.
 Approvals: UL
 listed./FM
 approved."

**Grand
Total:**

2343187.906

Twenty-
Three
Lakh
Forty-
Three
Thousand
One
Hundred
and
Eighty-
Seven
point
Nine Zero
Six

This Price and Delivery Schedule for Goods (Form e-PG2-2A) is Electronically Signed by Mr. Md Islam on behalf of S.S. Enterprise

S.S. Enterprise										
Price and Completion Schedule for Related Services (Form e- PG2-2B)										
Price and Completion Schedule for Related Services										
Item No.	Description of Item	Measurement Unit	Quantity	Point of Completion	Completion Period (In days)	Country of Origin	Unit Price in Figure (BDT)	Unit Price in Words (BDT)	Total Price in Figure (BDT)	Total Price in Words (BDT)
1	Related jobs	Item	1.000	PSTP Compound	60	Local	2000.001	Two Thousand point Zero Zero One	2000.001	Two Thousand point Zero Zero One
								Grand Total:	2000.001	Two Thousand point Zero Zero One

This Price and Completion Schedule for Related Services (Form e- PG2-2B) is Electronically Signed by Mr. Md Islam on behalf of S.S. Enterprise