

DHAKA WATER SUPPLY & SEWERAGE AUTHORITY

Office of the Executive Engineer

Civil Maintenance Division



Dhaka WASA, Dhaka

6th floor, WASA Bhaban

98 Kazi Nazrul Islam avnue, Dhaka.

Name of the Work: Repair and maintenance of sewer line, water line and ancillary work at Mohakhali still tank-102, Shapla-204 Duaripara and officer's apartment-D1 Gulshana-2 quarter compound, Dhaka WASA

Sl no	Item PWD 2022	Description of the item	Quantity	Unit	Rate	Amount
1	26.45.6	Supplying different inside dia best quality uPVC pressure pipe for water supply having specific gravity 1.35 - 1.45, and other physical, chemical, themal, fire resistivity properties etc. as per BSTI approved manufacturer standards or ASTM, BS/ISO/IS standards fitted and fixed in position with sockets, bends, with all accessories such as Round grating/domed roof grating, bends, sockets etc. approved and accepted by the Engineer-in-charge. 60 mm dia wall thickness 3.0 mm - 3.9 mm	3.000	meter	571.000	1713.00
2	26.49.6	50 mm PP-R Union	3.000	each	1190.000	3570.00
3	26.08.1	Supplying, fitting and fixing of European type glazed porcelain low-down. The sanitary ware shall conform BDS1162:2014. The glaze shall be thoroughly fused to body. The mean value of water absorption shall not be greater than 0.5% of the ware when dry. When tested with chemical solutions (Acetic acid, Citric acid, Detergent, Hydrochloric acid, Sodium hydroxide, Sodium stearate and Sulfuric acid of various strength) as per BDS1162:2014 procedure, none of the test pieces should suffer any loss of reflectivity on the glaze. The fixture should be placed on walls or directly over water closet by necessary accessories, rowel plugs, making holes wherever required and mending good the damages and fitting, fixing & finishing etc. complete with all necessary fittings and connections approved and accepted by the Engineer- in- charge. Approx. 365 X 185 X 325 mm size, minimum 10.00 kg of weight	1.000	each	3608.000	3608.00
4	1	Head mason / Mosaic head mistry	3.000	each	800.000	2400.00
5	4	Ordinary labour	6.000	each	550.000	3300.00



6	26.43.3	Supplying different inside dia best quality uPVC soil, waste and ventilation pipe having specific gravity 1.35 - 1.45, wall thickness 2.5 mm - 3.0 mm, and other physical, chemical, themal, fire resistivity properties etc. as per BSTI approved manufacturer standards or ASTM, BS/ISO/IS standards fitting and fixing in position with sockets, bends, of uPVC Pipe with all accessories such as Round grating /domed roof grating bands, sockets etc. approved and accepted by the Engineer- in- charge. 150 mm inside dia wall thickness 4.5 mm - 5.2 mm	17.00	meter	1599.000	27183.00
7	26.56.3	100 mm dia uPVC Y or T - Y Cleanout	6.00	each	671.000	4026.00
8	26.56.4	100 mm dia uPVC 'P' or 'S' trap	6.00	each	440.000	2640.00
					Total TK.	48,440.00

In Word: Forty eight thousand four hundred forty taka Only.

রাজিয়া সুলতানা
উপ-সহকারী প্রকৌশলী
সি এম বিভাগ
ঢাকা ওয়ার্স।
৬/৭/২৬

রাহাত উন নবী
সহকারী প্রকৌশলী
সি এম বিভাগ
ঢাকা ওয়ার্স।
০৩০৭/২৬

মুস্তা সাহা
নির্বাহী প্রকৌশলী
সিএম বিভাগ
ঢাকা ওয়ার্স
০৬/০৭/২৬